



FOR ALL B&D COLLECTIONS

THERE'S SO MUCH MORE BEHIND A  DOOR

# Door Comparison

## ROLLING DOORS

FEATURE COMPARISON	ROLLMASTA	FIRMADOOR	ROLL-A-DOOR (SQUARELINE DELUXE)
Mini groove topsheet for seamless operation	No	No	Yes
Separator to eliminate paint rub	No	No	Yes
Lifting handle for increased ease of operation	No	No	Yes
Bottom guide block to provide smooth operation in the guide channels	Single Roller	Single Roller	Double Roller
Bottom weatherseal to help stop leaves and rain coming in under the door	Yes	Yes	Yes
Flat in curtain at bottom rail for increased performance and aesthetic appeal	No	No	Yes
Spring life to ensure your door continues to operate like new	10,000 cycles	15,000 cycles	20,000 cycles
Warranty for increased peace of mind	1 Year	3 Years (pro rata) on door curtain, 1 year on surface and other parts.	7 Years on door curtain, 1 year on surface and other parts.
Centre lift lock with deep finger recess	No	No	Yes
Drums	Polypropylene	Steel	Steel
Tapers for sloping floors	Yes	Yes	Yes
Option of perforation for ventilation	No	Yes	Yes

## STEEL SECTIONAL DOORS

FEATURE COMPARISON	PANELMASTA	FIRMAPANEL	PANELIFT
Style options	3	2	6
Window options (based on door style)	up to 7	up to 6	up to 6
Colour matched window frames	White provided as standard. Colour match extra cost.	Yes*	Yes*
Pinchfree™ panels or hinges to stop finger entrapment on both the inside and outside of the door	No	No	Yes
Door tailor made for your home for improved appearance	Standard panel heights. Custom panel widths. Pressing spacing constant.	Custom panel heights and widths. Evenly spaced pressings to match width.	Custom panel heights and widths. Evenly spaced pressings to match width.
Rolled over edges to reduce the risk of cut fingers	Single rolled edge on reinforcing and panels.	Single rolled edge on reinforcing and panels.	Double rolled edge on panels, and single rolled on reinforcing.
In-line wheels and track to stop finger entrapment at the sides of the door	No	No	Yes
Reinforcing rail end caps protect against cuts from reo edges	Yes	Yes	Yes
Bottom weatherseal to help stop leaves and rain coming in under the door	Yes	Yes	Yes
Glass reinforced polypropylene track curve, for reduced headroom and smooth, quiet opening and closing	No	No	Yes
Polypropylene hinges and track curve reduces the chance of the door binding	No	No	Yes
Factory fitted, internal hinging system, reduces the need to maintain or lubricate hinges	No	No	Yes
In-line wheels and tracks, internal hinging system and fully enclosed stiles, for a clean uncluttered appearance on the inside of the door	No	No	Yes
Spring life to ensure your door continues to operate like new	10,000 cycles	15,000 cycles	20,000 cycles
Optional nylon hinges for quieter operation	Yes	No	N/A
Optional stainless steel cables for coastal locations	No	No	Yes
Tapers for sloping floors	Yes	Yes	Yes
Warranty for increased peace of mind	1 year	1 year	5 year

\*Window frames and trims do not colour match Timbagrain doors.

09/12



**Doors & Openers®**

THERE'S SO MUCH MORE BEHIND A B&D DOOR

Call **13 62 63** or visit [www.bnd.com.au](http://www.bnd.com.au) for further information

B&D Doors & Openers is a division of B&D Australia Pty Ltd, an Alesco Company ABN 25 010 473 971 © 2012 B&D Australia



FOR ALL B&amp;D COLLECTIONS

# Opener Comparison

## STANDARD FEATURES

FEATURE	SECTIONAL, FLEX-A-DOOR AND TILTING DOORS			ROLLING DOORS		
	CAD S	CAD P DIAMOND	CAD P DIAMOND WQ - WHISPER QUIET	CAD DIAMOND PD	FIRMAMATIC	SHED MASTER
Pulling force	700N	1000N	800N	550N	450N	450N
Motor	DC	DC	DC	DC	DC	DC
Automatic force sensing	✓	✓	✓	✓	✓	✓
Soft start / soft stop	✓	✓	✓	✓	✓	✓
Standby power consumption	2.2W	2.2W	2.2W	2W	2.2W	2.8W
Drive	Chain	Chain	Belt			
Rail system	Steel C-Rail, single and multi piece pre-assembled	Aluminium C-Rail pre-assembled	Aluminium C-Rail pre-assembled			
Maximum recommended door size (area)	16.5m <sup>2</sup>	18m <sup>2</sup>	18m <sup>2</sup>	16.5m <sup>2</sup>	15m <sup>2</sup>	15m <sup>2</sup>
Courtesy light	Festoon globe	120W	120W	2 LEDs	2 LEDs	
Courtesy light time	3 min	4 min (adjustable)	4 min (adjustable)	Adjustable	3 min (adjustable)	
Water resistant housing						✓
Lockable control panel and manual release						✓
Operating frequency	Tri-Tran™ technology. UHF multi frequency FM	Tri-Tran™ technology. UHF multi frequency FM	Tri-Tran™ technology. UHF multi frequency FM	Tri-Tran™ technology. UHF multi frequency FM	Tri-Tran™ technology. UHF multi frequency FM	TrioCode™
Receiver type	Multi channel frequency hopping	Multi channel frequency hopping	Multi channel frequency hopping	Multi channel frequency hopping	Multi channel frequency hopping	Multi channel frequency hopping
Two button transmitter	✓ x 1				✓ x 2	✓ x 2
4 button keyring transmitter	✓ x 1	✓ x 3	✓ x 3	✓ x 2		
Wall push button	✓	✓	✓			
Entry keypad		✓	✓			
Memory registers	8	14	14	14	8	8
Automatic close timer (requires safety infra-red beams to be activated)		✓	✓	✓		
Noise reducing chain clips		✓	N/A			
Warranty	5 year / 10,000 cycles	5 year / 10,000 cycles	5 year / 10,000 cycles	5 year / 10,000 cycles	2 year / 5,000 cycles	2 year parts only



## Doors & Openers®

THERE'S SO MUCH MORE BEHIND A B&amp;D DOOR

Call **13 62 63** or visit [www.bnd.com.au](http://www.bnd.com.au) for further information

B&amp;D Doors &amp; Openers is a division of B&amp;D Australia Pty Ltd, an Alesco Company ABN 25 010 473 971 © 2012 B&amp;D Australia